



- A For models 1200 amps maximum. Other sizes on demand.
- B Stainless steel is Nema 4X when lower hatch is closed.
- C Fi = camlocks for phases are female, camlok for neutral and grounding are male. Mi = camlocks for phases are male, camlok for neutral and grounding are female.
- D Grounding, green camlok, counts as 1 pole.
- E Contact STA BOXES to request special options. Requested options: _____
- F All boxes with camlok in front have mounting feet to be added to the height as well as lifting eye.

Certified according to rules CSA 22.2

BOX DIMENSIONS								Depth includes the cabinet and door thickness.	
TYPE OF BOXES	AMPERAGE	HEIGHT		WIDTH		DEPTH			
		inch	metric	inch	metric	inch	metric		
Nema 3R	Camlok	100/200	22"	559mm	20"	508mm	10"	254mm	
		400	26"	660mm	27"	685mm	11"	280mm	
		600/800	30"	762mm	36"	915mm	13"	330mm	
		1200	30"	762mm	36"	915mm	17"	432mm	
		1600	38"	965mm	44"	1118mm	17"	432mm	
	2000	38"	965mm	48"	1219mm	20"	508mm		
	Camlok mounting in front Note F	1600/2000	53"/69"	1346/1753mm	50"	1270mm	22"	559mm	
		2400/2800/3200	51"/67"	1296/1702mm	67"	1702mm	22"	559mm	
		3600/4000	66"/76"	1676/1930mm	74"	1880mm	25"	635mm	
	Camlok with disconnect	100	26"	660mm	21"	533mm	11"	280mm	
200		33"	838mm	22"	559mm	11"	280mm		
400		43"	1092mm	24"	610mm	13"	330mm		
600		50"	1270mm	28"	711mm	17"	432mm		
800		57"	1405mm	36"	915mm	19"	508mm		
1200		57"	1448mm	36"	915mm	18"	457mm		
Nema 1	Camlok	200 (Mini)	17"	432mm	8,5"	216mm	7"	178mm	
		200	19"	482mm	20"	508mm	6,5"	165mm	
		400	21"	533mm	19"	508mm	9"	228mm	
		600/800	34"	864mm	30"	762mm	13"	330mm	
	Camlok with disconnect	1200	36"	915mm	30"	762mm	17"	432mm	
		100/200	21"	553mm	19"	482mm	7"	178mm	
		400	24"	610mm	24"	610mm	10"	254mm	
		600	40"	1016mm	30"	762mm	13"	330mm	



Assembled cable available



Mounting feet available



Mini Nema 1